



Product Service

CERTIFICATE

No. Z1 022430 0062 Rev. 00

Holder of Certificate: **Alu Rehab AS**



Bedriftsvegen 23
4353 Klepp Stasjon
NORWAY

Certification Mark:



Product: **Standard wheelchairs**
Manual wheelchair

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713216465

Valid until: 2027-02-23

Date, 2022-03-07

(Torsten Zimmer)

CERTIFICATE

No. Z1 022430 0062 Rev. 00

Model(s): **Netti 4U Base (704764Netti4UBASEAB)**
Netti 4U CE (704764Netti4UCEEW)
Netti 4U CE Plus (704764Netti4UPLUS2V)

Parameters:

	Netti 4U Base	Netti 4U CE	Netti 4U CE Plus
total length incl. footrests:	1110 - 1130 mm	1130 mm	960 - 1160
width:	530 - 680 mm	530 - 680 mm	530 - 680 mm
height:	1150 mm (w/o head rest)	1030 mm (w/o head rest)	1100 mm (w/o head rest)
seat width:	350, 400, 450, 500 mm	400, 450, 500 mm	350, 400, 450, 500 mm
seat depth:	400, 425, 450, 475, 500 mm	425, 450, 475, 500 mm	
seat height at front edge:	465 - 500 mm (w/o seat cushion)		
backrest height:	500 mm (w/o seat cushion)	480 mm (w/o seat cushion)	500 mm (w/o seat cushion)
seat plane angle:	-8° - +22°	-5° - +20° (manually adjustable)	
backrest angle:	92° - 137°	92° - 137°	90 - 135° (manually adjustable)
max. user weight:	135 kg		
brake system:	drum brake (assistant brake)	knee lever brake (user brake)	
back wheels:			
- size	16 x 1 3/4", 16 x 1 3/8", 22 x 1", 22 x 1 3/8", 24 x 1", 24 x 1 3/8"		
- tyres	solid PU (puncture proof)		
- adjustable	yes		
- fixation	quick release		
front wheels:			
- size	Ø 175 x 33 mm; Ø 175 x 45 mm		
- tyres	solid PU (puncture proof)		
- adjustable	yes		
- fixation	quick release		
frame material:	aluminum		
arm support:	depth adjustable, upward swingable, not removable	depth and height adjustable, removable	
leg support:	height, angle adjustable, removable		
anti-tip device:	adjustable		

Tested according to: EN 12183:2014